Novatech®

Urbania & Loft Aluminum Patio Doors





Urbania & Loft Aluminum Patio Doors

Courage changes everything. That's why our engineers set out to reinvent the aluminum patio door. Offering high performance and a panoramic view in a wide two panel configuration, Urbania and Loft will blend your living space with the outdoors turning your home into a place for memorable gatherings with family and friends.

Panoramic View

Enjoy your living space to the fullest with a door that makes the outdoors an essential extension of your home. With wide glass panels and thin frames, Urbania & Loft provide a stunning panoramic view.

Effortless Operation

Tandem wheels and the available lift & slide mechanism make sliding oversized panels frictionless. Each detail is designed to make opening and closing simple, light, and enjoyable.

Exceptional Comfort and Energy Efficiency

Composite thermal barriers and an innovative sealing system combined to offer the highest performance ratings on the market. Urbania and Loft are certified for all ENERGY STAR zones without restrictions.

Aluminum Durability

Resistance to heat, cold, and to corrosion, as well as its superior durability make aluminum the best choice for a long lasting, maintenance-free product, specially for dark painted doors.

Enhanced Security

Urbania & Loft are engineered with the utmost structural integrity to withstand wind loads, shocks, and the toughest climates. Built with standard multi-point locking mechanisms, these doors will give you the peace of mind you deserve.


- 1. Contemporary style handle
- 2. 3" sash width for a maximised window surface
- 3. Black warm edge spacer
- 4. Thermally broken aluminum frame and sash
- 5. Clean and simple design and finish
- 6. Anodized aluminum sill

2



Loft: Think Bigger!

Get inspired and dare to choose a patio door as big as your expectations for new construction and renovation projects alike. Easy to operate, Loft's oversized panel creates a wide, open passage to the outdoors, bridging your living spaces seamlessly. Give yourself a view that will let your home breathe.



Large Two Panel Doors

Loft's lift and slide mecanism makes it possible to build sizable patio doors with only two panels for an impressive and uncluttered panoramic view.



Lift & Slide

Pivot the sleek, contemporary style handle to release the three-point locking mechanism and raise the door onto its wheels. Free from the friction of the gaskets and seals, the large panel weighing up to 250 lbs glides quietly and effortlessly with just one hand.








Asymmetrical Configuration

The combination of an impressively wide fixed sash with the ease of operation of a smaller and lighter sliding door. This configuration is a perfect complement to today's trends in home fenestration.



Urbania sliding patio door, $107\,\%'' \times 95\,\%''$ with asymetrical opening panel, sidelite and transom



Urbania sliding patio door, $107 \frac{1}{4}$ " $\times 95 \frac{1}{2}$ " with asymetrical opening panel

Urbania Sliding Patio Door

- Two-lite configurations up to 10 feet in width
- · Double-point locking mechanism for optimal security
- Superior performance
- Clean and simple design and finish
- Asymmetrical configuration available
- Low emissivity insulated glass unit with argon gas (Low E)
- Black warm edge spacer
- · Anodized aluminum sill cover
- · Corrosion resistant tandem wheels



Loft lift & slide patio door, 119"×95½"

Loft

Lift & Slide Patio Door


- + Lift and slide mechanism for an oversized sliding panel
- + Engineered for very large formats in two-lite configurations up to 12 feet in width
- + Triple-point locking mechanism for maximum security
- Superior performance
- Clean and simple design and finish
- · Asymmetrical configuration available
- Low emissivity insulated glass unit with argon gas (Low E)
- Black warm edge spacer
- · Anodized aluminum sill cover
- Corrosion resistant tandem wheels

Urbania	5' 6'		8'	9' × 0		
→	0 × 0 ×		0 ×	0 ×		
79½″ Height (2019mm)	59½" 71½" (1511mm) (1816mm)		95½" (2426mm)	107" (2718mm)		
81″ Height (2057mm)	58½" 70½" (1486mm) (1791mm)		94½" (2400mm)	107" (2718mm)		
95½" Height (2426mm)	59½" 71½" (1511mm) (1816mm)		95½" (2426mm)	107" (2718mm)		
		7'	8′	9'	10'	
→		×o	x o	x o	x o	
Asymmetrical Operating Panel	Available left or right hand					
79½" Height (2019mm)		83½ " (2121mm)	95¼" (2419mm)	107¼" (2724mm)	119¼″ (3029mm)	-
81″ Height (2057mm)		82½ " (2096mm)	94¾" (2407mm)	106¾" (2711mm)	118¾" (3016mm)	
95½" Height (2426mm)		83½" (2121mm)	95¼" (2419mm)	107¼" (2724mm)	119¼" (3029mm)	
		30" clearance	30" clearance	30" clearance	42" clearance	
	6'		8'	9'	10'	12'
Loft	× o		× o	× o	× o	× o
-	• ×		0 X	0 X	0 ×	0 X
79½″Height	71½"		95½"	107"	119"	143″

→			0 ×	0 ×	0 ×	0 X
79½" Height (2019mm)	71½" (1816mm)		95½" (2426mm)	107" (2718mm)	119" (3 022 mm)	143" (3 632 mm)
81″ Height (2057mm)	70½ " (1791mm)		94½ " (2400mm)	107" (2718mm)	119" (3 022 mm)	143" (3 632 mm)
95½"Height (2426mm)	71½" (1816mm)		95½" (2426mm)	107" (2718mm)	119" (3 022 mm)	143" (3 632 mm)
Asymmetrical Operating Panel	Available left or right hand	7' × 0	8'	9'	10' × 0	
79½" Height (2019mm)		83½" (2121mm)	95¼" (2419mm)	107¼" (2724mm)	119¼″ (3029mm)	
81" Height (2057mm)		82½" (2096mm)	94 ¾" (2 407 mm)	106¾" (2711mm)	118¾" (3016mm)	
95½" Height (2426mm)		83½" (2121mm)	95¼" (2419mm)	107¼" (2724mm)	119¼" (3 029 mm)	
		30" clearance	30" clearance	30" clearance	42" clearance	

Options

Options



Configuration Options

Custom sizes Sidelites and transoms Custom colors $1\,\%''$ Triple-pane insulated glass with Low E glass * $1\,\ensuremath{\e$

Accessory Options

Grids* Keyed lock (Urbania) Stainless Steel corrosion resistant double-point locking mecanism (Urbania) Ultra-resistant screen with 3" aluminum frame

* Options only available for some door configurations.

Installation Options

Frame width: 6", 7¼", 8", or 9¼" Nailing fin (width behind nailing fin: 4 % ", or 6 % ") Aluminum brick moulding Interior drywall moulding Sill extension

Specifications

Performance Reference: 95½″×95½″ door	Insulated Glass	1" double-pane with one Low E 80/70 glass	1¼" triple-pane with one Low E 80/70 glass* (Option)	1¼" triple-pane with dual Low E 80/70 glass* (Option)
	U Value ** W/m ² K	1.87	1.53	1.31
	Btu/(hr °F ft²)	0.33	0.27	0.23
	Energy Rating ***	31	35	38
	ENERGY STAR	Zones 1, 2	Zones 1, 2, 3	Zones 1, 2, 3


Air: A3

Water: DP 50 (360 Pa) Structural: LC 40 without reinforcement, CW 60 with reinforcement (Option) Condensation Resistance Index: I=53 Thermal Cycling tested ranging from -30 to 72 °C

Noise Reduction:

4mm + 4mm Insulated Glass: STC 31, OITC 24 4mm + 6mm Insulated Glass (Option): STC 35, OITC 28

Frame Configurations Multiple configurations to simplify installation for various wall depths.



- * Options only available for some door configurations.
- ** The U Value is the insulated glass' capacity to resist the transfer of heat. The lower this value, the better the window insulates.
- *** The Energy Rating balances a product's U Value with its solar heat gain and airtightness. A higher value indicates a more energy efficient product.

Novatech®

novatechgroup.com

Toll Free: 1-866-886-2215 Customer Service #1 quotesppn@novatechgroup.com ordersppn@novatechgroup.com Technical Service #2 savppn@novatechgroup.com

